

DESCAFLEX HAR-300 flat

0,50 mm² - 0,75 mm²

Cables PVC 300 V, H03VVH2-F flat

Application

Flexible electric cables for use in industrial, commercial and domestic premises.

Construction

Flexible bare copper conductors, acc. to IEC 60228, class 5
Insulation PVC
Coloured cores according to HD 308 S2
Sheath PVC, white, black or grey

Part Number	Type n x mm ²	Overall-Ø ca. mm	Copper kg/km	Weight kg/km
210865	2 x 0,50 wh	3.20 x 5.20	9.60	31.00
210860	2 x 0,50 bk	3.20 x 5.20	9.60	31.00

wh = white bk = black gr = grey



Technical Properties

Rated voltage U ₀ /U	300 / 300 V
Test voltage	2000 V
Insulation resistance	20 MΩm x km
Temperature range	- 5°C ... + 70°C
- static installation	- 30°C ... + 70°C
Minimum bending radius	15 x cable diameter

Standards / Approvals

CENELEC HD 21.5 S3

Part Number	Type n x mm ²	Overall-Ø ca. mm	Copper kg/km	Weight kg/km
210867	2 x 0,75 wh	3.40 x 5.60	14.40	33.00
210862	2 x 0,75 bk	3.40 x 5.60	14.40	33.00
210872	2 x 0,75 gr	3.40 x 5.60	14.40	33.00

Packaging

Coils of 100 m