

DESCAFLEX UL-3266

AWG 26 – AWG 10

Litzen 125°C 300 V UL-3266 / CSA

Querschnitt AWG	schwarz	blau	grün-gelb	braun	grau	rot	weiss	grün	orange	violett	gelb	rosa
26/7	126200	126202	126204	126206	126208	126210	126212	126214	126216	126218	126220	126222
26/19	126230	126232	126234	126236	126238	126240	126242	126244	126246	126248	126250	126252
24/7	126260	126262	126264	126266	126268	126270	126272	126274	126276	126278	126280	126282
24/19	126290	126292	126294	126296	126298	126300	126302	126304	126306	126308	126310	126312
22/7	126320	126322	126324	126326	126328	126330	126332	126334	126336	126338	126340	126342
22/19	126350	126352	126354	126356	126358	126360	126362	126364	126366	126368	126370	126372
20/7	126380	126382	126384	126386	126388	126390	126392	126394	126396	126398	126400	126402
20/19	126410	126412	126414	126416	126418	126420	126422	126424	126426	126428	126430	126432
18/7	126440	126442	126444	126446	126448	126450	126452	126454	126456	126458	126460	126462
18/19	126470	126472	126474	126476	126478	126480	126482	126484	126486	126488	126490	126492
16/19	126500	126502	126504	126506	126508	126510	126512	126514	126516	126518	126520	126522
16/26	126530	126532	126534	126536	126538	126540	126542	126544	126546	126548	126550	126552
14/19	126560	126562	126564	126566	126568	126570	126572	126574	126576	126578	126580	126582
14/41	126590	126592	126594	126596	126598	126600	126602	126604	126606	126608	126610	126612
12/19	126620	126622	126624	126626	126628	126630	126632	126634	126636	126638	126640	126642
12/65	126650	126652	126654	126656	126658	126660	126662	126664	126666	126668	126670	126672
10/37	126680	126682	126684	126686	126688	126690	126692	126694	126696	126698	126700	126702
10/105	126710	126712	126714	126716	126718	126720	126722	126724	126726	126728	126730	126732

auf Anfrage

UL Style 3271 600 V 125°C (AWG 30 – AWG 200 MCM)