

DESCAPREN UL-3289

AWG 24 – AWG 4/0

Halogen-free stranded wires 155°C 600 V UL-3289 / CSA

Application

As halogen-free, flame retardant UL/CSA approved stranded wire for the wiring of electrical panels, switchgears, electrical and electronic equipments, etc. and as a connection wire for motor and transformer windings, chokes and relays, which are subjected to an impregnation and/or as a connecting wire in an environment that demands a high temperature resistance.

Construction

Flexible tinned copper conductors
Insulation Polyolefin, high temperature resistant


Special Characteristics

Halogen-free/ Proof	IEC 60754-1	VDE 0472-815
Gases corrosivity	IEC 60754-2	VDE 0472-813
Flame retardant	IEC 60332-1	VDE 0472-804 B
Smoke density	IEC 61034-1+2	VDE 0472-816

Ozone, oxygen and weather-resistant, resistant to varnish and impregnation process, good oil and gasoline resistance.

Cross section AWG	Overall-Ø ca. mm	Copper kg/km	Weight kg/km
24	2.20	2.20	6.20
22	2.35	3.40	7.70
20	2.60	6.00	10.60
18	2.80	8.30	14.30
16	3.10	13.00	18.80
14	3.40	21.00	26.40
12	4.00	33.00	39.00
10	4.70	51.00	58.50
8	6.25	83.00	114.00
6	8.00	130.00	185.00
4	9.50	222.00	275.00
2	11.10	351.00	370.00
1	13.00	421.00	510.00
1/0	13.90	517.00	570.00
2/0	16.40	647.00	730.00
3/0	17.60	816.00	970.00
4/0	18.40	1047.00	1080.00

Colour code see next page



Technical Properties

Rated voltage U _o /U	600 V
Test voltage	3500 V
Temperature range	- 30°C ... + 155°C
Minimum bending radius	6 x outer diameter

Standards / Approvals

UL	AWM 3289	600 V	150°C
CSA	AWM I A/B	600 V	150°C

All packagings are delivered with UL + CSA Labels.

Packaging	Dimension
Spool 200 m	(160 x 90 x Centre 60 mm)
Spool 200 m	(160 x 90 x Centre 60 mm)
Spool 200 m	(160 x 90 x Centre 60 mm)
Spool 200 m	(160 x 90 x Centre 60 mm)
Spool 100 m	(160 x 90 x Centre 60 mm)
Spool 100 m	(160 x 90 x Centre 60 mm)
Spool 100 m	
Spool 100 m	
Spool 100 m	
Spool 100 m	
Drum	cut to desired length
Drum	cut to desired length
Drum	cut to desired length
Drum	cut to desired length
Drum	cut to desired length
Drum	cut to desired length
Drum	cut to desired length

on request

in barrels, UL Style 3271 600 V 125°C (AWG 30 – AWG 200 MCM)

DESCAPREN UL-3289

AWG 24 – AWG 4/0

Halogen-free stranded wires 155°C 600 V UL-3289 / CSA

Colour code							
AWG 24	black	blue	green-yellow	brown	grey	red	white
Spool 200 m	114010	114014	114018	114022	114026	114034	114038
	green	orange	violet	yellow	rose		
Spool 200 m	114042	114046	114050	114054	114058		
AWG 22	black	blue	green-yellow	brown	grey	red	white
Spool 200 m	114080	114084	114088	114092	114096	114104	114108
	green	orange	violet	yellow	rose		
Spool 200 m	114112	114116	114120	114124	114128		
AWG 20	black	blue	green-yellow	brown	grey	red	white
Spool 200 m	114150	114154	114158	114162	114166	114174	114178
	green	orange	violet	yellow	rose		
Spool 200 m	114182	114186	114190	114194	114198		
AWG 18	black	blue	green-yellow	brown	grey	red	white
Spool 200 m	114220	114224	114228	114232	114236	114244	114248
	green	orange	violet	yellow	rose		
Spool 200 m	114252	114256	114260	114264	114268		
AWG 16	black	blue	green-yellow	brown	grey	red	white
Spool 100 m	114290	114294	114298	114302	114306	114314	114318
	green	orange	violet	yellow	rose		
Spool 100 m	114322	114326	114330	114334	114338		
AWG 14	black	blue	green-yellow	brown	grey	red	white
Spool 100 m	114360	114364	114368	114372	114376	114384	114388
	green	orange	violet	yellow	rose		
Spool 100 m	114392	114396	114400	114404	114408		
AWG 12	black	blue	green-yellow	brown	grey		
Spool 100 m	114430	114434	114438	114442	114446		
AWG 10	black	blue	green-yellow	brown	grey		
Spool 100 m	114500	114504	114508	114512	114516		
AWG 8	black	blue	green-yellow	brown	grey		
Spool 100 m	114570	114572	114574	114576	114578		
AWG 6	black	blue	green-yellow	brown	grey		
Spool 100 m	114615	114617	114619	114621	114623		
AWG 4	black	blue	green-yellow	brown	grey		
Drum	114661	114663	114665	114667	114669		
AWG 2	black	blue	green-yellow	brown	grey		
Drum	114700	114701	114702	114703	114704		
AWG 1	black	green-yellow					
Drum	114710	114712					
AWG 1/0	black	green-yellow					
Drum	114716	114718					
AWG 2/0	black	green-yellow					
Drum	114724	114726					
AWG 3/0	black	green-yellow					
Drum	114732	114734					
AWG 4/0	black	green-yellow					
Drum	114740	114742					

on request

in barrels, UL Style 3271 600 V 125°C (AWG 30 – AWG 200 MCM)