



DESCATUBE 22P1

Polyester sleeves heat resistant + 130°C, class B

0,50 mm - 12 mm

Internal wiring of rotating and static machines in classes B and of hermetically closed units, sleeves for cable harnessing (automotive industry, electronics, light fittings), etc.

Construction	Braided polyester sleeves, slightly impregnated Color white	
Technical Data	Dielectric strength (in dry)	800 – 1200 V
	Temperature range	+ 130°C
Standards / Approvals	IEC 60684-1, IEC- 60684-2, IEC 60684-3 Teil 320	

Excellent mechanical resistance, high resistance to oils, alcohols and solvents, high resistance to freon gas, compatible with most impregnation varnishes.

Technical Information

Article number	Inner- Ø mm	Tolerance +/- mm	Wall thickness min. mm	Weight kg/km
806220	0,50	0.25	0.20	1.40
806222	0,80	0.25	0.20	1.70
806224	1,00	0.25	0.20	1.80
806226	1,50	0.25	0.20	2.00
806228	2,00	0.25	0.20	2.60
806230	2,50	0.25	0.20	3.00
806232	3,00	0.50	0.20	3.50
806234	3,50	0.50	0.20	3.80
806236	4,00	0.50	0.30	4.20
806238	4,50	0.50	0.30	7.50
806240	5,00	0.50	0.30	8.00
806242	6,00	0.50	0.30	10.00
806244	7,00	0.50	0.30	12.00
806246	8,00	0.50	0.30	15.30
806248	9,00	0.50	0.30	18.00
806250	10,00	0.50	0.40	20.00
806252	12,00	1.00	0.40	24.00

Packaging

0.50 – 4.50 mm coils of 200 m
 5 – 8 mm coils of 100 m
 9 – 12 mm coils of 50 m

Stock availability

Item numbers marked in **bold** are generally available from stock available, subject to prior sale.

On request

Up to inner-Ø 25 mm possible