



## DESCATUBE 33SI

Silica fibre sleeves heat resistant + 900°C

0,50 mm - 20 mm

Protection of cable harnessing or ducts at very high temperature, in Industrial ovens and stoves, etc.

|                       |                                                                                    |           |
|-----------------------|------------------------------------------------------------------------------------|-----------|
| Construction          | Silica fibre braided sleeves, untreated<br>non-impregnated<br>Color white (nature) |           |
| Technical Data        | Temperature range                                                                  | + 900°C   |
|                       | - Max. peak temperature                                                            | + 1'050°C |
| Standards / Approvals | IEC 60684-1, IEC- 60684-2                                                          |           |

High chemical resistance especially to acids, excellent thermal performance, incombustible, very highly flexible, expandable, low density, completely free of asbestos, frays slightly when cut

## Technical Information

| Article-number | Inner-Ø<br>mm | Wall thickness<br>min. mm | Weight<br>kg/km |
|----------------|---------------|---------------------------|-----------------|
| 806590         | 1,00          | 0.20                      | 3.80            |
| 806592         | 2,00          | 0.20                      | 6.20            |
| 806594         | 3,00          | 0.20                      | 9.60            |
| 806596         | 4,00          | 0.30                      | 15.20           |
| 806598         | 5,00          | 0.30                      | 20.00           |
| 806600         | 6,00          | 0.30                      | 24.00           |
| 806602         | 7,00          | 0.30                      | 27.00           |
| 806604         | 8,00          | 0.30                      | 30.00           |
| 806606         | 10,00         | 0.40                      | 36.00           |
| 806608         | 12,00         | 0.40                      | 48.00           |
| 806610         | 14,00         | 0.40                      | 66.00           |
| 806612         | 16,00         | 0.40                      | 80.00           |
| 806614         | 18,00         | 0.40                      | 88.00           |
| 806616         | 20,00         | 0.40                      | 94.00           |

### Packaging

0,50 – 4,50 mm spools of 200 m  
 5 – 20 mm spools of 100 m

### Stock availability

Item numbers marked in **bold** are generally available from stock, subject to prior sale.

### Remark

The extreme flexibility of these insulating/protective conduits makes it impossible to specify a tolerance for the inner diameter.