



PVC isolated wire for wiring in communications, electrical and electronics equipments, etc.

<b>Construction</b>	Solid tinned copper conductors Insulation PVC	
<b>Technical Data</b>	Rated voltage U <sub>0</sub> /U	max. 250 V
	Test voltage	2000 V
	Temperature range	- 5°C ... + 70°C
	Minimum bending radius	6 x outer diameter
<b>Standards / Approvals</b>	-	
	-	
	-	

## Technical Information

Cross section mm <sup>2</sup>	Outer-Ø ca. mm	Copper kg/km	Weight kg/km
0,50	1.10	1.90	2.80
0,60	1.20	2.90	3.40
0,80	1.40	4.80	6.00

0,50 mm <sup>2</sup>	black	light blue	green-yellow	brown	grey	dark blue	red
<b>PU</b>							
Spool 200m	152080	152081	152082	152083	152084	152085	152086

0,50 mm <sup>2</sup>	white	green	orange	violet	yellow	rose
<b>PU</b>						
Spool 200m	152087	152088	152089	152090	152091	152092

0,50 mm <sup>2</sup>	black	light blue	green-yellow	brown	grey	dark blue	red
<b>PU</b>							
Spool 200m	152100	152101	152102	152103	152104	152105	152106

0,60 mm <sup>2</sup>	white	green	orange	violet	yellow	rose	brown-white	Yellow-white
<b>PU</b>								
Spool 200m	152107	152108	152109	152110	152111	152112	152114	152115

0,80 mm <sup>2</sup>	black	light blue	green-yellow	brown	grey	dark blue	red
<b>PU</b>							
Spool 200m	152120	152121	152122	152123	152124	152125	152126

0,80 mm <sup>2</sup>	white	green	orange	violet	yellow	rose	brown-white
<b>PU</b>							
Spool 200m	152127	152128	152129	152130	152131	152132	152133

0,80 mm <sup>2</sup>	grey-white	yellow-white	green-white
<b>PU</b>			
Spool 200m	152134	152135	152136

### On request

In other versions and packaging

### Stock availability

Item numbers marked in **bold** are generally available from stock, subject to prior sale

Packaging	Dimension
Spool 200 m	135 x 75 x center 60 mm